



pears.AddRecoveryHours



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."AddRecoveryHours"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "tfrom" TIME,IN "tto" TIME,IN "hrs" SMALLINT )  
RETURNS TIME  
BEGIN  
  DECLARE "rv" TIME;  
  IF "isnull"("hrs",0) <= 0 OR "tfrom" IS NULL OR "tto" IS NULL THEN  
    RETURN "tto"  
  END IF;  
  IF "hrs" > 23 THEN  
    SET "hrs" = 23  
  END IF;  
  SET "rv" = "dateadd"("hour","hrs","tto");  
  IF "rv" < "tto" AND "rv" >= "tfrom" THEN  
    SET "rv" = "dateadd"("minute",-1,"tfrom")  
  END IF;  
  RETURN "rv"  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_addrecoveryhours

Last update: 2026/08/07 19:24

