



pears.AWRPlacement



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."AWRPlacement"( IN "vacid" CHAR(20),IN "persid"
CHAR(20),IN "shiftid" CHAR(20) )
RETURNS CHAR(20)
BEGIN
    DECLARE "rv" CHAR(20);
    -- finds placementid for use in AWR
    SET "rv" = NULL;
    IF "shiftid" IS NOT NULL THEN
        SELECT "placementid" INTO "rv" FROM "tempshift" WHERE "tempshiftid" =
"shiftid"
    END IF;
    IF "rv" IS NULL THEN
        SELECT FIRST "placementid" INTO "rv" FROM "placement" KEY JOIN
"employment" WHERE "personid" = "persid" AND "vacancyid" = "vacid" ORDER BY
"isnull"("employment"."leavedate",CURRENT DATE+3650) DESC
    END IF;
    IF "rv" IS NULL THEN
        -- set rv = uniquekey(persid);
        -- insert into placement () values () ;
        -- might create one and return ID ???
    END IF;
    RETURN "rv"
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_awrplacement

Last update: 2026/08/07 19:24

