



pears.BlobstoreDeleteExternal



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."BlobstoreDeleteExternal"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "xpath" CHAR(250) )  
RETURNS INTEGER  
NOT deterministic  
BEGIN  
  DECLARE "delcmd" CHAR(10);  
  IF "isnull"("xpath",'') <> '' THEN  
    IF "right"("BlobstoreDbFolder"(),1) = '/' THEN -- sp_delete_file AVs if  
file does not exist so avoid  
      SET "delcmd" = 'rm '  
    ELSE  
      SET "delcmd" = 'del '  
    END IF;  
    RETURN "xp_cmdshell"("delcmd"+"BlobstoreFullPath"("xpath"),'no_output')  
    -- Will be 0 if the file was successfully deleted  
  ELSE  
    RETURN 0  
  END IF  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_blobstoredeleteexternal

Last update: 2026/08/07 19:24

