



# pears.BlobstoreFetch



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

## Original SQL

```
CREATE FUNCTION "pears"."BlobstoreFetch"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "blobclass" CHAR(1),IN "blobid" CHAR(20) )  
RETURNS long BINARY  
BEGIN  
  DECLARE "xpath" CHAR(250);  
  DECLARE "dat" long BINARY;  
  SELECT "externalfilepath","blob" INTO "xpath","dat" FROM "blobstore" WHERE  
"class" = "blobclass" AND "id" = "blobid";  
  IF "dat" IS NULL AND "trim"("isnull"("xpath",'')) <> '' THEN  
    SET "dat" = "xp_read_file"("BlobstoreFullPath"("xpath"))  
  END IF;  
  RETURN "dat"  
END
```

From:  
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:  
[https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears\\_blobstorefetch](https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_blobstorefetch)

Last update: 2026/08/07 19:24

