



pears.BlobstoreRelocate



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."BlobstoreRelocate"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "blobclass" CHAR(1),IN "blobid" CHAR(20) )  
RETURNS INTEGER  
NOT deterministic  
BEGIN  
  DECLARE "z" INTEGER;  
  DECLARE "xpath" CHAR(250);  
  DECLARE "xfolder" CHAR(250);  
  DECLARE "bAlreadyExists" INTEGER;  
  SELECT 1,"trim"("externalfilepath") INTO "bAlreadyExists","xpath" FROM  
"blobstore" WHERE "class" = "blobclass" AND "id" = "blobid";  
  IF "bAlreadyExists" IS NULL THEN  
    return -1 -- Row not found  
  END IF;  
  SET "xfolder" = "BlobStoreExtFolder"(NULL);  
  IF "xfolder" IS NULL AND "isnull"("xpath",'') = '' THEN  
    RETURN 0 -- Nothing to do  
  END IF;  
  IF "xfolder" IS NOT NULL AND "isnull"("xpath",'') <> '' THEN  
    RETURN 0 -- Nothing to do  
  END IF;  
  SET "z" = "BlobstoreRead"("blobclass","blobid",NULL);  
  IF "z" IS NULL THEN  
    return -1 -- Row not found (redundant check)  
  ELSE  
    RETURN "BlobStoreWrite"("blobclass","blobid","z",NULL)  
  END IF  
END
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_blobstorerelocate

Last update: **2026/08/07 19:24**

