



pears.CollectionDeleteAllowed



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."CollectionDeleteAllowed"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "pCollectionid" CHAR(20) )  
RETURNS long VARCHAR  
BEGIN  
    DECLARE "rv" long VARCHAR;  
    DECLARE "collectioncount" INTEGER;  
    SET "rv" = '';  
    IF NOT EXISTS(SELECT * FROM "collection" WHERE "collectionid" =  
"pCollectionid") THEN  
        RETURN "string"('Collection not found')  
    END IF;  
    SELECT "count"() INTO "collectioncount" FROM "collection" WHERE "parent" =  
"pCollectionid";  
    IF "collectioncount" > 0 THEN  
        SET "rv" = "string"('Collection has ', "collectioncount", ' children')  
    END IF;  
    SELECT "count"() INTO "collectioncount" FROM "collectionchat" WHERE  
"collectionid" = "pcollectionid";  
    IF "collectioncount" > 0 THEN  
        SET "rv" = "trim"("string"("rv", "char"(13), "char"(10), 'Collection has  
, "collectioncount", ' messages'))  
    END IF;  
    RETURN "rv"  
END
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_collectiondeleteallowed

Last update: 2026/08/07 19:24

