



pears.ComplianceValidforPlacement



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."ComplianceValidforPlacement"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "pPersonID" CHAR(20),IN "pVacancyID" CHAR(20) )  
RETURNS long VARCHAR  
BEGIN  
  DECLARE "pComplianceDomainID" CHAR(20);  
  DECLARE "pClientCode" CHAR(12);  
  DECLARE "pDate" DATE;  
  DECLARE "pDeptID" CHAR(2);  
  SELECT  
    "v"."ComplianceDomainID","v"."StartDate","v"."DepartmentID","c"."TempComplianceCode"  
    INTO "pComplianceDomainID","pDate","pDeptID","pClientCode" FROM  
    "vacancy" AS "v" KEY JOIN "employment" JOIN "company" AS "c" WHERE  
    "v"."vacancyid" = "pVacancyID";  
  IF "pDate" IS NULL OR "pDate" < CURRENT DATE THEN  
    SET "pDate" = CURRENT DATE  
  END IF;  
  IF "pComplianceDomainID" IS NULL THEN  
    SELECT FIRST "ComplianceDomainID" INTO "pComplianceDomainID" FROM  
    "ComplianceDomain" WHERE "DepartmentID" = "pDeptID" AND "Name" LIKE  
    'Default%'  
    AND("ClientTempComplianceCode" IS NULL OR "ClientTempComplianceCode" =  
    "pClientCode")  
    ORDER BY "ClientTempComplianceCode" DESC,"Name" ASC  
  END IF;  
  IF "pComplianceDomainID" IS NOT NULL THEN  
    RETURN  
    "ComplianceValid"("pPersonID","pComplianceDomainID","pDate","pClientCode")  
  END IF  
END
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_compliancevalidforplacement

Last update: **2026/08/07 19:24**

