



# pears.DBCleanupOrphanOLEDocument



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

## Original SQL

```
CREATE FUNCTION "pears"."DBCleanupOrphanOLEDocument"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "countordo" CHAR(1) )  
RETURNS INTEGER  
BEGIN  
    DECLARE @RC INTEGER;  
    SET @RC = 0;  
    IF "countordo" = 'C' THEN  
        SELECT "count"() INTO @RC FROM "OLEDocument"  
            WHERE(((("ownertype" = 'P') AND NOT EXISTS(SELECT * FROM "person" WHERE  
"personid" = "OLEDocument"."ownerid"))  
            OR(("ownertype" = 'C') AND NOT EXISTS(SELECT * FROM "company" WHERE  
"companyid" = "OLEDocument"."ownerid"))  
            OR(("ownertype" = 'V') AND NOT EXISTS(SELECT * FROM "vacancy" WHERE  
"vacancyid" = "OLEDocument"."ownerid"))  
            OR(("ownertype" = 'R') AND NOT EXISTS(SELECT * FROM "progress" WHERE  
"progressid" = "OLEDocument"."ownerid"))  
            OR(("ownertype" = 'L') AND NOT EXISTS(SELECT * FROM "placement" WHERE  
"placementid" = "OLEDocument"."ownerid"))));  
        RETURN @RC  
    END IF;  
    DELETE FROM "OLEDocument" WHERE("ownertype" = 'P')  
        AND NOT EXISTS(SELECT * FROM "person" WHERE "personid" =  
"OLEDocument"."ownerid");  
    SET @RC = @RC+(SELECT @@rowcount);  
    DELETE FROM "OLEDocument" WHERE("ownertype" = 'C')  
        AND NOT EXISTS(SELECT * FROM "company" WHERE "companyid" =  
"OLEDocument"."ownerid");  
    SET @RC = @RC+(SELECT @@rowcount);  
    DELETE FROM "OLEDocument" WHERE("ownertype" = 'V')  
        AND NOT EXISTS(SELECT * FROM "vacancy" WHERE "vacancyid" =  
"OLEDocument"."ownerid");  
    SET @RC = @RC+(SELECT @@rowcount);  
    DELETE FROM "OLEDocument" WHERE("ownertype" = 'R')  
        AND NOT EXISTS(SELECT * FROM "progress" WHERE "progressid" =
```



```
"OLEDocument"."ownerid");  
SET @RC = @RC+(SELECT @@rowcount);  
DELETE FROM "OLEDocument" WHERE("ownertype" = 'L')  
AND NOT EXISTS(SELECT * FROM "placement" WHERE "placementid" =  
"OLEDocument"."ownerid");  
SET @RC = @RC+(SELECT @@rowcount);  
CALL "AuditLog"('CLEANUP',NULL,"string"(@RC,' Unattached OLEDocument  
Records deleted '),NULL,NULL);  
RETURN @RC  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

[https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears\\_dbcleanuporphanoledocument](https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_dbcleanuporphanoledocument)

Last update: 2026/08/07 19:24

