



pears.DBCleanupOrphanPhone



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."DBCleanupOrphanPhone"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "countordo" CHAR(1) )  
RETURNS INTEGER  
BEGIN  
  DECLARE @RC INTEGER;  
  SET @RC = 0;  
  IF "countordo" = 'C' THEN  
    SELECT "count"() INTO @RC FROM "phone"  
      WHERE(((("who" = 'P') AND NOT EXISTS(SELECT * FROM "person" WHERE  
"personid" = "phone"."whoid"))  
      OR(("who" = 'C') AND NOT EXISTS(SELECT * FROM "company" WHERE  
"companyid" = "phone"."whoid"))  
      OR(("who" = 'CP') AND NOT EXISTS(SELECT * FROM "employment" WHERE  
"employmentid" = "phone"."whoid"))));  
    RETURN @RC  
  END IF;  
  DELETE FROM "phone" WHERE("who" = 'P')  
    AND NOT EXISTS(SELECT * FROM "person" WHERE "personid" =  
"phone"."whoid");  
  SET @RC = @RC+(SELECT @@rowcount);  
  DELETE FROM "phone" WHERE "who" = 'CP'  
    AND NOT EXISTS(SELECT * FROM "employment" WHERE "employmentid" =  
"phone"."whoid");  
  SET @RC = @RC+(SELECT @@rowcount);  
  DELETE FROM "phone" WHERE("who" = 'C')  
    AND NOT EXISTS(SELECT * FROM "company" WHERE "companyid" =  
"phone"."whoid");  
  SET @RC = @RC+(SELECT @@rowcount);  
  CALL "AuditLog"('CLEANUP',NULL,"string"(@RC,' Unattached Phone Records  
deleted '),NULL,NULL);  
  RETURN @RC  
END
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_dbcleanuporphanphone

Last update: **2026/08/07 19:24**

