



pears.depttran



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."depttran"( IN "deptu" CHAR(1) )
RETURNS CHAR(2)
BEGIN
  DECLARE "rv" CHAR(2);
  CASE "deptu"
  WHEN '0' THEN SET "rv" = '0'
  WHEN 'B' THEN SET "rv" = 'CN'
  WHEN 'H' THEN SET "rv" = 'CT'
  WHEN 'J' THEN SET "rv" = 'CU'
  WHEN 'G' THEN SET "rv" = 'DR'
  WHEN 'A' THEN SET "rv" = 'EN'
  WHEN 'C' THEN SET "rv" = 'FA'
  WHEN 'F' THEN SET "rv" = 'MI'
  WHEN 'E' THEN SET "rv" = 'WR'
  ELSE
    SET "rv" = 'ZC'
  END CASE;
  RETURN("rv")
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_depttran

Last update: **2026/08/07 19:24**

