



pears.GetCompanyAddressOnLine



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetCompanyAddressOnLine"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "reqcompanyid" CHAR(20) )  
RETURNS CHAR(250)  
BEGIN  
    DECLARE "AddressOnLine" CHAR(250);  
    DECLARE "addr1" CHAR(40);  
    DECLARE "addr2" CHAR(40);  
    DECLARE "addr3" CHAR(40);  
    DECLARE "town" CHAR(30);  
    DECLARE "county" CHAR(30);  
    DECLARE "country" CHAR(30);  
    DECLARE "postcode" CHAR(30);  
    SELECT  
        "company"."addr1", "company"."addr2", "company"."addr3", "company"."town", "comp  
any"."county", "company"."country", "company"."postcode" INTO "addr1",  
        "addr2", "addr3", "town", "county", "country", "postcode" FROM "company"  
        WHERE "companyid" = "reqcompanyid";  
    IF "isnull"("addr1", '') <> '' THEN SET "AddressOnLine" = "AddressOnLine"  
    || "trim"("addr1")  
    END IF;  
    IF "isnull"("AddressOnLine", '') <> '' AND "isnull"("addr2", '') <> '' THEN  
SET "AddressOnLine" = "AddressOnLine" || ', '  
    END IF;  
    IF "isnull"("addr2", '') <> '' THEN SET "AddressOnLine" = "AddressOnLine"  
    || "trim"("addr2")  
    END IF;  
    IF "isnull"("AddressOnLine", '') <> '' AND "isnull"("addr3", '') <> '' THEN  
SET "AddressOnLine" = "AddressOnLine" || ', '  
    END IF;  
    IF "isnull"("addr3", '') <> '' THEN SET "AddressOnLine" = "AddressOnLine"  
    || "trim"("addr3")  
    END IF;  
    IF "isnull"("AddressOnLine", '') <> '' AND "isnull"("town", '') <> '' THEN  
SET "AddressOnLine" = "AddressOnLine" || ', '
```



```
END IF;
IF "isnull"("town",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine" ||
"trim"("town")
END IF;
IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("county",'') <> '' THEN
SET "AddressOnLine" = "AddressOnLine" || ', '
END IF;
IF "isnull"("county",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine"
|| "trim"("county")
END IF;
IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("country",'') <> ''
THEN SET "AddressOnLine" = "AddressOnLine" || ', '
END IF;
IF "isnull"("country",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine"
|| "trim"("country")
END IF;
IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("postcode",'') <> ''
THEN SET "AddressOnLine" = "AddressOnLine" || ', '
END IF;
IF "isnull"("postcode",'') <> '' THEN SET "AddressOnLine" =
"AddressOnLine" || "trim"("postcode")
END IF;
RETURN "AddressOnLine"
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getcompanyaddressonline

Last update: 2026/08/07 19:24

