



pears.GetCompanyGroupHead



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetCompanyGroupHead"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "CompID" CHAR(20) )  
RETURNS CHAR(20)  
BEGIN  
  DECLARE "coid" CHAR(20);  
  DECLARE "oldcoid" CHAR(20);  
  DECLARE "lc" INTEGER;  
  SELECT "parentcompanyid" INTO "coid" FROM "company" WHERE "companyid" =  
"compid";  
  IF "coid" IS NULL THEN  
    RETURN "compid"  
  END IF;  
  SET "oldcoid" = NULL;  
  SET "lc" = 1;  
  while("coid" IS NOT NULL) AND("lc" < 1000) loop  
    SET "oldcoid" = "coid";  
    SET "lc" = "lc"+1;  
    SELECT "parentcompanyid" INTO "coid" FROM "company" WHERE "companyid" =  
"coid"  
  END loop;  
  RETURN "oldcoid"  
END
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getcompanygrouphead

Last update: 2026/08/07 19:24

