



pears.GetKeyShiftPlanState



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetKeyShiftPlanState"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "sid" CHAR(20),IN "ddate" DATE,IN "bperson" SMALLINT )  
RETURNS CHAR(21)  
BEGIN  
  DECLARE "rv" CHAR(21);  
  IF "bperson" = 1 THEN  
    RETURN NULL  
  ELSE  
    SET "rv"  
      = "isnull"(  
        (SELECT FIRST "string"(IF "cascadelevel" > 0 THEN 'Y' ELSE 'X'  
endif,"tempshiftplanid") FROM "tempshiftplan" AS "p"  
          WHERE "vacancyid" = "sid" AND "shiftdate" = "ddate"  
          AND NOT "tempshiftplanid" = any(SELECT "tempshiftplanid" FROM  
"tempshift" WHERE "vacancyid" = "p"."vacancyid"  
          AND "shiftdate" = "ddate" AND(NOT("state" = 'C' AND "crefill" =  
1)) AND "tempshiftplanid" IS NOT NULL) ORDER BY "cascadelevel" DESC),  
        (SELECT FIRST "string"("state","tempshiftid") FROM "tempshift"  
          WHERE "vacancyid" = "sid" AND "shiftdate" = "ddate"  
AND(NOT("tempshift"."state" = 'C' AND "tempshift"."clientconfirmed" = 1))  
AND "tempshift"."state" <> 'U' ORDER BY(CASE "state" WHEN 'P' THEN 1  
          WHEN 'C' THEN 2 WHEN 'B' THEN 3 ELSE 4 END) ASC))  
      END IF;  
  RETURN "rv"  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getkeyshiftplanstate

Last update: 2026/08/07 19:24

