



pears.GetPayOrCharge



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetPayOrCharge"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "PayOrCharge" CHAR(1),IN "PlacOrVac" CHAR(1),IN "ID" CHAR(20) )  
RETURNS CHAR(20)  
BEGIN  
  DECLARE "pay" DOUBLE;  
  DECLARE "istemp" SMALLINT;  
  IF "placorvac" = 'P' THEN  
    SELECT "isnull"("temp",0),"salary" INTO "istemp","pay" FROM "placement"  
WHERE "placementid" = "id"  
  ELSE  
    SELECT "isnull"("temp",0),"salary" INTO "istemp","pay" FROM "vacancy"  
WHERE "vacancyid" = "id"  
  END IF;  
  IF "istemp" = 0 THEN  
    IF "payorcharge" = 'P' THEN  
      RETURN "commathousands"("pay")  
    ELSE  
      RETURN ''  
    END IF  
  ELSE RETURN  
"trim"("str"("gettemprate"("payorcharge","placorvac","id"),20,2))  
  END IF  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getpayorcharge

Last update: 2026/08/07 19:24

