



# pears.GetPersonAddressOnLine



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

## Original SQL

```
CREATE FUNCTION "pears"."GetPersonAddressOnLine"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "reqpersonid" CHAR(20) )  
RETURNS CHAR(250)  
BEGIN  
  DECLARE "AddressOnLine" CHAR(250);  
  DECLARE "addr1" CHAR(40);  
  DECLARE "addr2" CHAR(40);  
  DECLARE "addr3" CHAR(40);  
  DECLARE "town" CHAR(30);  
  DECLARE "county" CHAR(30);  
  DECLARE "country" CHAR(30);  
  DECLARE "postcode" CHAR(30);  
  SELECT  
    "person"."addr1","person"."addr2","person"."addr3","person"."town","person".  
    "county","person"."country","person"."postcode" INTO "addr1",  
      "addr2","addr3","town","county","country","postcode" FROM "person"  
      WHERE "personid" = "reqpersonid";  
  IF "isnull"("addr1",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine"  
  || "trim"("addr1")  
  END IF;  
  IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("addr2",'') <> '' THEN  
SET "AddressOnLine" = "AddressOnLine" || ', '  
  END IF;  
  IF "isnull"("addr2",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine"  
  || "trim"("addr2")  
  END IF;  
  IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("addr3",'') <> '' THEN  
SET "AddressOnLine" = "AddressOnLine" || ', '  
  END IF;  
  IF "isnull"("addr3",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine"  
  || "trim"("addr3")  
  END IF;  
  IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("town",'') <> '' THEN  
SET "AddressOnLine" = "AddressOnLine" || ', '
```



```
END IF;
IF "isnull"("town",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine" ||
"trim"("town")
END IF;
IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("county",'') <> '' THEN
SET "AddressOnLine" = "AddressOnLine" || ', '
END IF;
IF "isnull"("county",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine"
|| "trim"("county")
END IF;
IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("country",'') <> ''
THEN SET "AddressOnLine" = "AddressOnLine" || ', '
END IF;
IF "isnull"("country",'') <> '' THEN SET "AddressOnLine" = "AddressOnLine"
|| "trim"("country")
END IF;
IF "isnull"("AddressOnLine",'') <> '' AND "isnull"("postcode",'') <> ''
THEN SET "AddressOnLine" = "AddressOnLine" || ', '
END IF;
IF "isnull"("postcode",'') <> '' THEN SET "AddressOnLine" =
"AddressOnLine" || "trim"("postcode")
END IF;
RETURN "AddressOnLine"
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

[https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears\\_getpersonaddressonline](https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getpersonaddressonline)

Last update: 2026/08/07 19:24

