



pears.GetPersonPhoneInBlock



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetPersonPhoneInBlock"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "reqpersonid" CHAR(20) )  
RETURNS long VARCHAR  
BEGIN  
  DECLARE "phones" long VARCHAR;  
  DECLARE "newline" CHAR(2);  
  DECLARE "loopcounter" tinyint;  
  DECLARE "tab" CHAR(1);  
  DECLARE "TabString" CHAR(2);  
  SET "newline" = "char"(13)+"char"(10);  
  SET "phones" = '';  
  SET "loopcounter" = 0;  
  SET "tab" = "char"(9);  
  FOR "fetchfor" AS "fetchcursor" no scroll cursor FOR  
    SELECT "phonetype"."name" AS "nextname", "phone"."number" AS "nextnumber"  
  FROM "phone"  
    KEY JOIN "phonetype" WHERE "phone"."who" = 'P' AND "whoid" =  
    "reqpersonid"  
    ORDER BY "phone"."whoid" ASC, "phonetype"."sortorder"  
  ASC, "phonetype"."name" ASC FOR READ ONLY do  
    IF "loopcounter" > 0 THEN  
      SET "phones" = "phones" || "newline"  
    END IF;  
    IF "length"("nextname") < 8 THEN SET "TabString" = "Tab"+"Tab"  
    ELSE SET "TabString" = "Tab"  
    END IF;  
    SET "phones" = "phones" || "nextname" || "TabString" || "nextnumber";  
    SET "loopcounter" = "loopcounter"+1 END FOR;  
  RETURN "phones"  
END
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getpersonphoneinblock

Last update: **2026/08/07 19:24**

