



pears.GetPlacementTheirRef



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetPlacementTheirRef"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "persid" CHAR(20),IN "vacid" CHAR(20) )  
RETURNS CHAR(50)  
BEGIN  
  DECLARE "rv" CHAR(50);  
  SET "rv" = NULL;  
  "forstat": FOR "forlab" AS "curs" no scroll cursor FOR  
    SELECT "placement"."theirref" FROM "placement" KEY JOIN "employment"  
      WHERE "placement"."vacancyid" = "vacid" AND "employment"."personid" =  
"persid"  
      AND "placement"."temp" <> 0 ORDER BY  
"isnull"("employment"."leavedate",CURRENT DATE+3650) DESC FOR READ ONLY do  
    SET "rv" = "theirref";  
  leave "forstat" END FOR;  
  IF "trim"("isnull"("rv",'')) = '' THEN  
    SELECT "theirref" INTO "rv" FROM "vacancy" WHERE "vacancyid" = "vacid"  
  END IF;  
  RETURN("rv")  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getplacementtheirref

Last update: **2026/08/07 19:24**

