



pears.GetQuestAnswer



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetQuestAnswer"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "tagloc" CHAR(3),IN "tagid" CHAR(3),IN "parentid" CHAR(20) )  
RETURNS long VARCHAR  
BEGIN  
  DECLARE "rv" long VARCHAR;  
  DECLARE "i" INTEGER;  
  SET "rv" = "getquesttext"("tagloc","tagid","parentid");  
  IF "rv" IS NULL THEN  
    RETURN(NULL)  
  END IF;  
  SET "i" = "locate"("rv","char"(13));  
  IF "i" > 0 THEN  
    SET "rv" = "left"("rv","i"-1)  
  END IF;  
  SET "i" = "locate"("rv","char"(9));  
  IF "i" >= "length"("rv") THEN  
    RETURN('')  
  END IF;  
  IF "i" > 0 THEN  
    SET "rv" = "stuff"("rv",1,"i",'')  
  END IF;  
  RETURN("rv")  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getquestanswer

Last update: 2026/08/07 19:24

