



pears.GetTempName



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."GetTempName"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "persid" CHAR(20) )  
RETURNS CHAR(60)  
BEGIN  
  DECLARE "rv" CHAR(60);  
  SELECT "string"(IF EXISTS(SELECT * FROM "wpkglobalswitchsetting" WHERE  
"wpkglobalswitchid" = 'USEFULLNAME' AND "location" = 'Global' AND "value" =  
'Y') THEN "person"."name"  
  ELSE  
"ifnull"("person"."surname","person"."name","string"("person"."surname",',',  
, "firstword"("person"."forenames")))  
  endif,(SELECT "string"(' (' , "name", ')') FROM "company" WHERE "companyid"  
= (SELECT "secondaryagencyid" FROM "pay_employee" WHERE "personid" =  
"persid")))  
  INTO "rv" FROM "person" WHERE "personid" = "persid";  
  RETURN "rv"  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_gettempname

Last update: 2026/08/07 19:24

