



# pears.getword



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

## Original SQL

```
CREATE FUNCTION "pears"."getword"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "s1" long VARCHAR, IN "ln1" SMALLINT )  
RETURNS CHAR(200)  
BEGIN  
  DECLARE "i" SMALLINT;  
  DECLARE "ln" SMALLINT;  
  DECLARE "s" CHAR(200);  
  SET "ln" = "ln1";  
  SET "s" = "s1";  
  "loop1": loop  
    SET "ln" = "ln"-1;  
    IF "ln" <= 0 THEN  
      leave "loop1"  
    END IF;  
    SET "i" = "charindex"("char"(32),"s");  
    IF "i" > 0 THEN  
      SET "s" = "stuff"("s",1,"i",'')  
    ELSE  
      SET "s" = ''  
    END IF  
  END loop "loop1";  
  SET "i" = "charindex"("char"(32),"s");  
  IF "i" > 0 THEN  
    SET "s" = "left"("s","i"-1)  
  END IF;  
  RETURN("s")  
END
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

[https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears\\_getword](https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_getword)



Last update: **2026/08/07 19:24**