



pears.IQXNetExtractParam



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."IQXNetExtractParam"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "pParams" long VARCHAR, IN "pParamName" CHAR(100) )  
RETURNS long VARCHAR  
deterministic  
BEGIN  
  DECLARE "v" long VARCHAR;  
  DECLARE "n" CHAR(100);  
  DECLARE "i" INTEGER;  
  SET "pParams" = "replace"("pParams","char"(10),'');  
  loop  
    SET "i" = "charindex"('=', "pParams");  
    IF "isnull"("i",0) = 0 THEN  
      RETURN NULL  
    END IF;  
    SET "n" = "left"("pParams","i"-1);  
    SET "pParams" = "stuff"("pParams",1,"i",'');  
    SET "i" = "charindex"("char"(13),"pParams");  
    IF "i" = 0 THEN  
      SET "v" = "pParams";  
      SET "pParams" = ''  
    ELSE  
      SET "v" = "left"("pParams","i"-1);  
      SET "pParams" = "stuff"("pParams",1,"i",'')  
    END IF;  
    IF "n" = "pParamName" THEN  
      RETURN "v"  
    END IF  
  END loop  
END
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_iqxnetextractparam

Last update: **2026/08/07 19:24**

