



pears.IQXNetHasPermission



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."IQXNetHasPermission"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "pWebUserID" CHAR(20), IN "pRightID" CHAR(20) )  
RETURNS SMALLINT  
NOT deterministic  
BEGIN  
  DECLARE "rv" SMALLINT;  
  SET "rv" = 0;  
  IF(SELECT FIRST "isnull"((SELECT FIRST "Assigned" FROM  
"IQXNetRightAssigned" WHERE "IQXNetRightID" = "a"."IQXNetRightID" AND  
"IQXNetUserID" = "u"."IQXNetUserID"),0)  
  +"isnull"((SELECT FIRST 1 FROM "IQXNetRightDefault" WHERE  
"IQXNetRightID" = "a"."IQXNetRightID" AND "IQXNetUserClassID" =  
"a"."IQXNetUserClassID" AND "ID" = "a"."ID"),0)  
  FROM "IQXNetRightAllowed" AS "a" JOIN "IQXNetUser" AS "u" ON  
"a"."IQXNetUserClassID" = "u"."IQXNetUserClassID" AND "a"."ID" = '*'  
  WHERE "u"."IQXNetUserID" = "pWebUserID" AND "a"."IQXNetRightID" =  
"pRightID") > 0 THEN  
    SET "rv" = 1  
  END IF;  
  RETURN "rv"  
END
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_iqxnethaspermission

Last update: **2026/08/07 19:24**

