



pears.IQXNetSwitchValue



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."IQXNetSwitchValue"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "pWebUserID" CHAR(20), IN "pIQXNetSwitchID" CHAR(50) )  
RETURNS CHAR(250)  
NOT deterministic  
BEGIN  
    DECLARE "irv" INTEGER;  
    DECLARE "rv" CHAR(250);  
    DECLARE "xIQXNetUserClassID" CHAR(20);  
    SELECT "IQXNetUserClassID" INTO "xIQXNetUserClassID" FROM "IQXNetUser"  
WHERE "IQXNetUserID" = "pWebUserID";  
    SELECT  
        "nullif"("IQXNetOverrideSwitchValue"("xIQXNetUserClassID", "pWebUserID", "IQXN  
etSwitchID", "Value"), 0),  
        "nullif"("trim"("IQXNetOverrideSwitchTextValue"("xIQXNetUserClassID", "pWebUs  
erID", "IQXNetSwitchID", "TextValue")), '')  
        INTO "irv", "rv" FROM "IQXNetSwitch" WHERE "IQXNetSwitchID" =  
"pIQXNetSwitchID";  
    IF "irv" IS NOT NULL THEN  
        RETURN "isnull"("rv", "string"("irv"))  
    END IF  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_iqxnetswitchvalue

Last update: 2026/08/07 19:24

