



pears.IQXNetTemplateChoiceList



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."IQXNetTemplateChoiceList"(  
  IN "templateid" CHAR(20),IN "deptid" CHAR(20) )  
RETURNS long VARCHAR  
BEGIN  
  DECLARE "rv" long VARCHAR;  
  DECLARE "xtagid" CHAR(20);  
  DECLARE "xchoiceid" CHAR(20);  
  DECLARE "xlocation" CHAR(20);  
  SELECT FIRST  
  "trim"("isnull"("tagid",'')), "trim"("isnull"("tagchoiceid",'')), "taglocation"  
  INTO "xtagid", "xchoiceid", "xlocation" FROM "tempshifttemplate" WHERE  
  "tempshifttemplateid" = "templateid";  
  IF "xlocation" = 'A' THEN  
    SET "xlocation" = "string"('A',"deptid")  
  END IF;  
  SET "rv" = NULL;  
  IF "xtagid" <> '' AND "xchoiceid" = '' THEN  
    SELECT "list"("string"("tagchoiceid",'~[',"description"), '~[' ORDER BY  
  "sortorder" ASC, "description" ASC) INTO "rv" FROM "tagchoice"  
    WHERE "taglocation" = "xlocation" AND "tagid" = "xtagid" AND  
  "isnull"("subchoice",0) = 0  
  END IF;  
  RETURN "rv"  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_iqxnettemplatechoicelist

Last update: 2026/08/07 19:24

