



pears.MakeKeyName



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."MakeKeyName" (  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "sSource" CHAR(60) )  
RETURNS CHAR(60)  
BEGIN  
  DECLARE "rv" CHAR(60);  
  DECLARE "isin" CHAR(50);  
  DECLARE "c" CHAR(1);  
  SET "rv" = '';  
  SET "isin" = 'ABCDEFGHIJKLMNOPQRSTUVWXYZ&0123456789';  
  SET "isin" = "isin"+"char"(39);  
  IF "isnull"((SELECT "removespacesfromkeynames" FROM "params"),0) = 0 THEN  
    SET "isin" = "isin"+" '  
  END IF;  
  SET "ssource" = "trim"("ucase"("csconvert"("ssource",'ascii')));  
  while "length"("ssource") > 0 loop  
    SET "c" = "left"("ssource",1);  
    IF "charindex"("c","isin") > 0 THEN  
      SET "rv" = "rv"+"c"  
    END IF;  
    SET "ssource" = "stuff"("ssource",1,1,'')  
  END loop;  
  IF "trim"("rv") = '' THEN SET "rv" = 'UNKNOWN' END IF;  
  RETURN("rv")  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_makekeyname

Last update: 2026/08/07 19:24

