



pears.MasterRosterTempAllowed



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."MasterRosterTempAllowed"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "ppersid" CHAR(20),IN "pmastershiftid" CHAR(20) )  
RETURNS INTEGER  
BEGIN  
  DECLARE "ionly" INTEGER;  
  DECLARE "iactive" INTEGER;  
  IF "pmastershiftid" IS NULL THEN  
    RETURN 1  
  END IF;  
  IF "ppersid" = (SELECT "defaultpersonid" FROM "masterrostershift" WHERE  
"masterrostershiftid" = "pmastershiftid") THEN  
    RETURN 1  
  END IF;  
  SELECT "isnull"("r"."useonlypreferred",0),"isnull"("p"."active",0) INTO  
"ionly","iactive"  
  FROM "masterrostershift" AS "s" KEY JOIN "masterroster" AS "r" LEFT  
OUTER JOIN "MasterRosterPreferredPerson" AS "p"  
  ON "r"."MasterRosterID" = "p"."MasterRosterID" AND "p"."PersonID" =  
"ppersid"  
  WHERE "s"."masterrostershiftid" = "pmastershiftid";  
  IF "ionly" = 0 THEN  
    RETURN 1  
  ELSE  
    RETURN "iactive"  
  END IF  
END
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_masterrostertempallowed

Last update: 2026/08/07 19:24



