



pears.PersonAvailableForRecovery



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."PersonAvailableForRecovery"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "sFoundDigit" CHAR(1),IN "sPersonid" CHAR(20),IN "dShiftDate" DATE,IN  
  "tShiftFrom" TIME,IN "tShiftTo" TIME,IN "iRecovery" SMALLINT,IN  
  "MovingShiftID" CHAR(20) )  
RETURNS CHAR(1)  
BEGIN  
  DECLARE "x" CHAR(1);  
  IF "isnull"("irecovery",0) = 0 OR "isnull"("sfounddigit",'A') <> 'A' THEN  
    RETURN "sfounddigit"  
  END IF;  
  SET "x" =  
  "personavailableforplaniterate"("spersonid","dshiftdate","tshiftfrom","addre  
coverhours"("tshiftfrom","tshiftto","irecovery"),0,"movingshiftid");  
  IF "isnull"("x",'A') = 'A' THEN  
    RETURN "sfounddigit"  
  ELSE  
    RETURN "x"  
  END IF  
END
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_personavailableforrecovery

Last update: 2026/08/07 19:24

