



pears.WPKLocalSwitchValue



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."WPKLocalSwitchValue"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "SwitchID" CHAR(20),IN "SwitchLocation" CHAR(20),IN "SwitchSource"  
  CHAR(1),IN "SwitchLocked" SMALLINT,IN "SwitchLocalisable" SMALLINT )  
  RETURNS long VARCHAR  
  BEGIN  
    DECLARE "rv" long VARCHAR;  
    SET "rv" = NULL;  
    IF "switchlocked" = 1 OR "switchsource" NOT IN( 'L','P' ) THEN -- Only  
      unlocked Literal and Params switches can be over-ridden in this way  
      RETURN "rv"  
    END IF;  
    IF "switchlocation" IS NOT NULL AND "switchlocalisable" = 1 THEN  
      SELECT FIRST "value" INTO "rv" FROM "wpkglobalswitchsetting" WHERE  
      "wpkglobalswitchid" = "switchid" AND "location" = "switchlocation"  
    END IF;  
    IF "switchsource" = 'L' AND "rv" IS NULL THEN -- Params continue to have  
      their global value stored in the params table  
      SELECT FIRST "value" INTO "rv" FROM "wpkglobalswitchsetting" WHERE  
      "wpkglobalswitchid" = "switchid" AND "location" = 'Global'  
    END IF;  
    RETURN "rv"  
  END
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_wpklocalswitchvalue

Last update: 2026/08/07 19:24

