



pears.wtd_start_of_hol_year



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE FUNCTION "pears"."wtd_start_of_hol_year"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "pid" CHAR(20),IN "yr" INTEGER,IN "wk" INTEGER )  
RETURNS DATE  
BEGIN  
  DECLARE "sdate" DATE;  
  DECLARE "wedate" DATE;  
  SET "wedate" = "date"("weekenddate"("yr","wk"));  
  IF "wedate" IS NULL THEN -- Off the range of known weeks  
    RETURN NULL  
  END IF;  
  SELECT "min"("startdate") INTO "sdate" FROM "pay_employment" WHERE  
"personid" = "pid"  
    AND("enddate" IS NULL OR "enddate" >= "wedate"-13); --(still working or  
stopped >= last week)  
  IF "sdate" IS NULL THEN  
    RETURN NULL  
  END IF;  
  SET "sdate" = "getholidayyear"("sdate","wedate"-7); --Does 1/10/1998  
threshold, and rolls forward if > 1 year ago  
  RETURN "sdate"  
END
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:functions:pears_wtd_start_of_hol_year

Last update: 2026/08/07 19:24

