



pears.AddPhone



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."AddPhone"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "cpe" CHAR(2),IN "ptype" CHAR(25),IN "recid" CHAR(20),IN "snumber"  
  CHAR(200) )  
BEGIN  
  DECLARE "tpid" CHAR(20);  
  DECLARE "sid" CHAR(20);  
  IF "trim"("isnull"("ptype",'')) = '' THEN  
    RETURN  
  END IF;  
  IF "trim"("isnull"("recid",'')) = '' THEN  
    RETURN  
  END IF;  
  IF "trim"("isnull"("snumber",'')) = '' THEN  
    RETURN  
  END IF;  
  IF "cpe" = 'E' THEN  
    SET "cpe" = 'CP'  
  END IF;  
  SET "tpid" = NULL;  
  IF "cpe" = 'C' THEN  
    SELECT "phonetypeid" INTO "tpid" FROM "phonetype" WHERE "name" = "ptype"  
  AND "company" = 1  
  ELSE IF "cpe" = 'P' THEN  
    SELECT "phonetypeid" INTO "tpid" FROM "phonetype" WHERE "name" =  
  "ptype" AND "applicant" = 1  
  ELSE IF "cpe" = 'CP' THEN  
    SELECT "phonetypeid" INTO "tpid" FROM "phonetype" WHERE "name" =  
  "ptype" AND "contact" = 1  
  END IF  
  END IF END IF;  
  IF "tpid" IS NULL THEN  
    RETURN  
  END IF;  
  SET "sid" = "uniquekey"('x');
```



```
INSERT INTO "phone"( "phoneid","phonetypeid","who","whoid","number" )
VALUES( "sid","tpid","cpe","recid","snumber" )
END
GO

COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."AddPhone" IS
{CREATE PROCEDURE AddPhone

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN cpe CHAR(2),IN ptype CHAR(25),IN recid CHAR(20),IN snumber CHAR(200))
BEGIN
    DECLARE tpid CHAR(20);
    DECLARE sid CHAR(20);
    IF TRIM(isnull(ptype,'')) = '' THEN
        RETURN
    END IF;
    IF TRIM(isnull(recid,'')) = '' THEN
        RETURN
    END IF;
    IF TRIM(isnull(snumber,'')) = '' THEN
        RETURN
    END IF;
    IF cpe = 'E' THEN
        SET cpe='CP'
    END IF;
    SET tpid=NULL;
    IF cpe = 'C' THEN
        SELECT phonetypeid INTO tpid FROM phonetype WHERE name = ptype AND
company = 1
    ELSE IF cpe = 'P' THEN
        SELECT phonetypeid INTO tpid FROM phonetype WHERE name = ptype AND
applicant = 1
    ELSE IF cpe = 'CP' THEN
        SELECT phonetypeid INTO tpid FROM phonetype WHERE name = ptype AND
contact = 1
    END IF
    END IF
    END IF;
    IF tpid IS NULL THEN
        RETURN
    END IF;
    SET sid=uniquekey('x');
    INSERT INTO phone(phoneid,phonetypeid,who,whoid,NUMBER)
VALUES(sid,tpid,cpe,recid,snumber)
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_addphone

Last update: **2026/08/07 19:24**

