



pears.BlobstoreDeleteExternal



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."BlobstoreDeleteExternal" IS
{CREATE FUNCTION BlobstoreDeleteExternal

/* Application Maintained Function / Procedure - DO NOT EDIT*/

( IN xpath CHAR(250) )
RETURNS INTEGER
NOT deterministic
BEGIN
    DECLARE delcmd CHAR(10);
    IF isnull(xpath,'') <> '' THEN
        IF RIGHT(BlobstoreDbFolder(),1)='/' THEN -- sp_delete_file AVs if file
does not exist so avoid
            SET delcmd='rm '
        ELSE
            SET delcmd='del '
        END IF;
        RETURN xp_cmdshell(delcmd+BlobstoreFullPath(xpath),'no_output') -- Will
be 0 if the file was successfully deleted
    ELSE
        RETURN 0
    END IF;
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_blobstoredeleteexternal

Last update: 2026/08/07 19:24

