



pears.BlobstoreRead



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."BlobstoreRead" IS
{CREATE FUNCTION BlobstoreRead

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN blobclass CHAR(1),IN blobid CHAR(20),IN requestedby CHAR(15))
RETURNS INTEGER
NOT deterministic
BEGIN
    DECLARE z INTEGER;
    DECLARE xpath CHAR(250);
    DECLARE dat long BINARY;
    SELECT isnull(zipped,0),TRIM(externalfilepath),BLOB INTO z,xpath,dat FROM
blobstore WHERE class = blobclass AND id = blobid;
    IF z IS NULL THEN
        RETURN NULL // No ROW
    END IF;
    IF dat IS NULL AND isnull(xpath,'') <> '' THEN
        SET dat=xp_read_file(BlobstoreFullPath(xpath))
    END IF;
    IF dat IS NULL THEN
        RETURN NULL // No BLOB
    END IF;
    IF varexists('iqblobtemp') = 0 THEN
        CREATE variable iqblobtemp long BINARY
    END IF;
    SET iqblobtemp=dat;
    IF requestedby IS NOT NULL THEN
        UPDATE blobstore SET accessedby = requestedby,accessedat = CURRENT
TIMESTAMP WHERE class = blobclass AND id = blobid
    END IF;
    RETURN z
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_blobstoreread

Last update: **2026/08/07 19:24**

