



pears.CollectionDelete



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."CollectionDelete"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "pCollectionID" CHAR(20) )  
RESULT( "pResult" CHAR(250) )  
BEGIN  
    IF EXISTS(SELECT * FROM "collection" WHERE "collectionid" =  
"pcollectionid") THEN  
        DELETE FROM "collection" WHERE "collectionid" = "pcollectionid";  
        SELECT '0:~Success'  
    ELSE SELECT '1:~Collection not found'  
    END IF  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."CollectionDelete" IS  
{CREATE PROCEDURE CollectionDelete  
  
/* Application Maintained Function / Procedure - DO NOT EDIT*/  
  
( IN pCollectionID CHAR(20) )  
RESULT (pResult CHAR(250))  
BEGIN  
    IF EXISTS(SELECT * FROM collection WHERE collectionid = pcollectionid)  
THEN  
        DELETE FROM collection WHERE collectionid = pcollectionid;  
        SELECT '0:~Success';  
    ELSE SELECT '1:~Collection not found';  
    END IF ;  
END  
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_collectiondelete

Last update: **2026/08/07 19:24**

