



pears.CollectionDeleteAllowed



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."CollectionDeleteAllowed" IS
{CREATE FUNCTION CollectionDeleteAllowed

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(pCollectionid CHAR(20))
RETURNS long VARCHAR
BEGIN
    DECLARE rv long VARCHAR;
    DECLARE collectioncount INTEGER;
    SET rv='';
    IF NOT EXISTS(SELECT * FROM collection WHERE collectionid =
pCollectionid) THEN
        RETURN "string"('Collection not found');
    END IF;
    SELECT COUNT(*) INTO collectioncount FROM collection WHERE parent =
pCollectionid;
    IF collectioncount>0 THEN
        SET rv = string('Collection has ',collectioncount,' children');
    END IF;
    SELECT COUNT(*) INTO collectioncount FROM collectionchat WHERE
collectionid = pcollectionid;
    IF collectioncount>0 THEN
        SET rv = TRIM( string( rv , CHAR(13), CHAR(10), 'Collection has
',collectioncount,' messages')));
    END IF;
    RETURN rv;
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_collectiondeleteallowed

Last update: **2026/08/07 19:24**

