



pears.CollectionsSetChat



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."CollectionsSetChat"(  
    /* Application Maintained Function / Procedure - DO NOT EDIT*/  
    IN "pCollectionID" CHAR(20), IN "pStaffID" CHAR(20), IN "pChatMessage" long  
    VARCHAR )  
RESULT( "presult" CHAR(50) )  
BEGIN  
    INSERT INTO "collectionchat"(  
        "collectionchatid", "collectionid", "staffid", "chatmessage", "chatdate" )  
    VALUES(  
        "uniquekey"("pcollectionid"), "pcollectionid", "pstaffid", "pchatmessage", CURRE  
        NT TIMESTAMP ) ;  
    SELECT '0:~Success'  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."CollectionsSetChat" IS  
{CREATE PROCEDURE CollectionsSetChat  
  
/* Application Maintained Function / Procedure - DO NOT EDIT*/  
  
(IN pCollectionID CHAR(20), IN pStaffID CHAR(20), pChatMessage Long VARCHAR)  
RESULT( presult CHAR(50))  
BEGIN  
    INSERT INTO collectionchat(collectionchatid, collectionid, staffid,  
        chatmessage, chatdate) VALUES(uniquekey(pcollectionid), pcollectionid,  
        pstaffid, pchatmessage, CURRENT TIMESTAMP);  
    SELECT '0:~Success';  
END  
}
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_collectionssetchat

Last update: **2026/08/07 19:24**

