



pears.CollectionsSetQuestions



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."CollectionsSetQuestions"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "pCollectionID" CHAR(20),IN "pQanswer" long VARCHAR )  
RESULT( "pResult" CHAR(250) )  
BEGIN  
  CALL "CollectionsSetQuestion"("pcollectionid","pQanswer");  
  SELECT '0:~Success'  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."CollectionsSetQuestions" IS  
{CREATE PROCEDURE CollectionsSetQuestions  
  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  
  ( IN pCollectionID CHAR(20),pQanswer long VARCHAR )  
  RESULT(pResult CHAR(250) )  
  BEGIN  
    CALL CollectionsSetQuestion(pcollectionid, pQanswer);  
    SELECT '0:~Success';  
  END  
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_collectionssetquestions

Last update: 2026/08/07 19:24

