



pears.DBCleanupOrphanTagValue



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."DBCleanupOrphanTagValue" IS
{CREATE FUNCTION DBCleanupOrphanTagValue

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN countordo CHAR(1))
RETURNS INTEGER
BEGIN
    DECLARE @RC INTEGER;
    SET @RC = 0;
    IF countordo = 'C' THEN
        SELECT COUNT(*) INTO @RC FROM tagvalue WHERE
        (
            (((taglocation = 'P') OR (taglocation LIKE 'A%')) AND NOT EXISTS(SELECT
* FROM person WHERE personid = tagvalue.id)) OR
            ((taglocation = 'E') AND NOT EXISTS(SELECT * FROM employment WHERE
employmentid = tagvalue.id)) OR
            ((taglocation = 'C') AND NOT EXISTS(SELECT * FROM company WHERE
companyid = tagvalue.id)) OR
            ((taglocation LIKE 'V%') AND NOT EXISTS(SELECT * FROM vacancy WHERE
vacancyid = tagvalue.id)) OR
            ((taglocation LIKE 'L%') AND NOT EXISTS(SELECT * FROM placement WHERE
placementid = tagvalue.id)) OR
            ((taglocation = 'U') AND NOT EXISTS(SELECT * FROM staff WHERE staffid =
tagvalue.id)) OR
            ((taglocation = 'N') AND NOT EXISTS(SELECT * FROM contactevent WHERE
contacteventid = tagvalue.id))
        );
        RETURN @RC
    END IF;
    DELETE FROM tagvalue WHERE((taglocation = 'P') OR(taglocation LIKE 'A%'))
AND
    NOT EXISTS(SELECT * FROM person WHERE personid = tagvalue.id);
    SET @RC = @RC + (SELECT @@rowcount);
    DELETE FROM tagvalue WHERE(taglocation = 'C') AND
```



```
NOT EXISTS(SELECT * FROM company WHERE companyid = tagvalue.id);
DELETE FROM tagvalue WHERE(taglocation = 'E') AND
NOT EXISTS(SELECT * FROM employment WHERE employmentid = tagvalue.id);
SET @RC = @RC + (SELECT @@rowcount);
DELETE FROM tagvalue WHERE(taglocation LIKE 'V%') AND
NOT EXISTS(SELECT * FROM vacancy WHERE vacancyid = tagvalue.id);
SET @RC = @RC + (SELECT @@rowcount);
DELETE FROM tagvalue WHERE(taglocation LIKE 'L%') AND
NOT EXISTS(SELECT * FROM placement WHERE placementid = tagvalue.id);
SET @RC = @RC + (SELECT @@rowcount);
DELETE FROM tagvalue WHERE(taglocation = 'U') AND
NOT EXISTS(SELECT * FROM staff WHERE staffid = tagvalue.id);
SET @RC = @RC + (SELECT @@rowcount);
DELETE FROM tagvalue WHERE(taglocation = 'N') AND
NOT EXISTS(SELECT * FROM contactevent WHERE contacteventid =
tagvalue.id);
SET @RC = @RC + (SELECT @@rowcount);
CALL AuditLog('CLEANUP',NULL,string(@RC,' Unattached Question Answers
deleted '),NULL,NULL);
RETURN @RC;
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_dbcleanuporphantagvalue

Last update: 2026/08/07 19:24

