



pears.DeleteOldDatabaseLogs



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."DeleteOldDatabaseLogs" IS
'create function DeleteOldDatabaseLogs

/* Application Maintained Function / Procedure - DO NOT EDIT*/

( in @DaysToKeep smallint )
returns smallint
begin
  --Deletes all files log files with pattern 000000AA.LOG in current log
  folder over a given age. Read only flags are ignored.
  declare @Command char(250);
  declare @Count smallint;
  declare @LogFilePathName char(250);
  declare @LogPath char(250);
  set @LogFilePathName = db_property('LogName');
  set @LogPath =
"left"(@LogFilePathName,locate(@LogFilePathName,'\\\\\\\\',-1)-1);
  set @Count = 0;
  for DeleteLoop as DeleteCursor no scroll cursor for
    select file_path as DeleteLogFilePathName
    from sp_list_directory(@LogPath)
    where file_type = 'F'
    and upper("right"(file_path,length(file_path)-
locate(file_path,'\\\\\\\\',-1))) regexp
'^[[:digit:]]{6}[[:alnum:]]{2}\\\\\\\\.LOG$'
    and modified_date_time < dateadd(day,(@DaysToKeep*-1),current date)
    and file_path <> @LogFilePathName for read only
  do
    set @Command = string('DEL /F "',DeleteLogFilePathName,'");
    call xp_cmdshell(@Command,'no_output');
    set @Count = @Count+1
  end for;
  return @Count
end'
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_deleteolddatabaselogs

Last update: **2026/08/07 19:24**

