



pears.FormatAddress



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."FormatAddress" IS
{CREATE FUNCTION FormatAddress

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN name CHAR(100),IN addr1 CHAR(50),IN addr2 CHAR(50),IN addr3 CHAR(50),IN
town CHAR(50),IN county CHAR(50),IN country CHAR(50),IN postcode CHAR(50),
IN Capitalise SMALLINT,IN STYLE CHAR(1)) /* Set the seperator for block or
line */ /* If capitalise option is set, capitalise town. */ /* Build
Formatted Address */
RETURNS CHAR(300) BEGIN DECLARE FormattedAddress CHAR(300);DECLARE Separator
CHAR(2);DECLARE PrePostCodeSeparator CHAR(2);SET FormattedAddress='';
  IF STYLE = 'B' THEN SET Separator="char"(13)+"char"(10);
    SET PrePostCodeSeparator=Separator
  ELSE SET Separator=', ';
    SET PrePostCodeSeparator=' '
  END IF;
  IF Capitalise = 1 THEN SET town=UPPER(Town)
  END IF;
  IF isnull(name,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(name)
  END IF;
  IF isnull(FormattedAddress,'') <> '' AND isnull(addr1,'') <> '' THEN SET
FormattedAddress=FormattedAddress || Separator
  END IF;
  IF isnull(addr1,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(addr1)
  END IF;
  IF isnull(FormattedAddress,'') <> '' AND isnull(addr2,'') <> '' THEN SET
FormattedAddress=FormattedAddress || Separator
  END IF;
  IF isnull(addr2,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(addr2)
  END IF;
  IF isnull(FormattedAddress,'') <> '' AND isnull(addr3,'') <> '' THEN SET
```



```
FormattedAddress=FormattedAddress || Separator
END IF;
IF isnull(addr3,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(addr3)
END IF;
IF isnull(FormattedAddress,'') <> '' AND isnull(town,'') <> '' THEN SET
FormattedAddress=FormattedAddress || Separator
END IF;
IF isnull(town,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(town)
END IF;
IF isnull(FormattedAddress,'') <> '' AND isnull(county,'') <> '' THEN SET
FormattedAddress=FormattedAddress || Separator
END IF;
IF isnull(county,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(county)
END IF;
IF isnull(FormattedAddress,'') <> '' AND isnull(country,'') <> '' THEN SET
FormattedAddress=FormattedAddress || Separator
END IF;
IF isnull(country,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(country)
END IF;
IF isnull(FormattedAddress,'') <> '' AND isnull(postcode,'') <> '' THEN
SET FormattedAddress=FormattedAddress || PrePostCodeSeparator
END IF;
IF isnull(postcode,'') <> '' THEN SET FormattedAddress=FormattedAddress ||
TRIM(postcode)
END IF;
RETURN FormattedAddress END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_formataddress

Last update: 2026/08/07 19:24

