



pears.FormatCompanyAddress1_0



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."FormatCompanyAddress1_0" IS
{CREATE FUNCTION FormatCompanyAddress1_0

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN reqcompanyid CHAR(20),IN Capitalise SMALLINT,IN STYLE CHAR(1))
RETURNS CHAR(300)
BEGIN
    DECLARE FormattedAddress CHAR(300);
    DECLARE addr1 CHAR(40);
    DECLARE addr2 CHAR(40);
    DECLARE addr3 CHAR(40);
    DECLARE town CHAR(30);
    DECLARE county CHAR(30);
    DECLARE country CHAR(30);
    DECLARE postcode CHAR(30);
    DECLARE Separator CHAR(2);
    DECLARE PrePostCodeSeparator CHAR(2);
    /*
    Set the separator for block or line
    */
    IF STYLE = 'B' THEN
        SET Separator="char"(13)+"char"(10);
        SET PrePostCodeSeparator=Separator
    ELSE SET Separator=', ';
        SET PrePostCodeSeparator=' '
    END IF;
    /*
    Fetch address fields
    */
    SELECT
company.addr1,company.addr2,company.addr3,company.town,company.county,compan
y.country,company.postcode INTO addr1,
    addr2,addr3,town,county,country,postcode FROM company WHERE
    companyid = reqcompanyid;
```



```
/*  
If capitalise option is set, capitalise town.  
*/  
IF Capitalise = 1 THEN SET town=UPPER(Town)  
END IF;  
/*  
Build Formatted Address  
*/  
IF isnull(addr1,'') <> '' THEN SET FormattedAddress=FormattedAddress ||  
TRIM(addr1)  
END IF;  
IF isnull(FormattedAddress,'') <> '' AND isnull(addr2,'') <> '' THEN SET  
FormattedAddress=FormattedAddress || Separator  
END IF;  
IF isnull(addr2,'') <> '' THEN SET FormattedAddress=FormattedAddress ||  
TRIM(addr2)  
END IF;  
IF isnull(FormattedAddress,'') <> '' AND isnull(addr3,'') <> '' THEN SET  
FormattedAddress=FormattedAddress || Separator  
END IF;  
IF isnull(addr3,'') <> '' THEN SET FormattedAddress=FormattedAddress ||  
TRIM(addr3)  
END IF;  
IF isnull(FormattedAddress,'') <> '' AND isnull(town,'') <> '' THEN SET  
FormattedAddress=FormattedAddress || Separator  
END IF;  
IF isnull(town,'') <> '' THEN SET FormattedAddress=FormattedAddress ||  
TRIM(town)  
END IF;  
IF isnull(FormattedAddress,'') <> '' AND isnull(county,'') <> '' THEN SET  
FormattedAddress=FormattedAddress || Separator  
END IF;  
IF isnull(county,'') <> '' THEN SET FormattedAddress=FormattedAddress ||  
TRIM(county)  
END IF;  
IF isnull(FormattedAddress,'') <> '' AND isnull(country,'') <> '' THEN SET  
FormattedAddress=FormattedAddress || Separator  
END IF;  
IF isnull(country,'') <> '' THEN SET FormattedAddress=FormattedAddress ||  
TRIM(country)  
END IF;  
IF isnull(FormattedAddress,'') <> '' AND isnull(postcode,'') <> '' THEN  
SET FormattedAddress=FormattedAddress || PrePostCodeSeparator  
END IF;  
IF isnull(postcode,'') <> '' THEN SET FormattedAddress=FormattedAddress ||  
TRIM(postcode)  
END IF;  
RETURN FormattedAddress
```



END

}

From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_formatcompanyaddress1_0

Last update: **2026/08/07 19:24**

