



pears.FormatSelfBillAddress



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."FormatSelfBillAddress" IS
{CREATE FUNCTION FormatSelfBillAddress

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(
  IN "reqAccountCode" CHAR(20),IN "Capitalise" SMALLINT,IN "Style" CHAR(1) )
RETURNS CHAR(300)
BEGIN
  DECLARE "FormattedAddress" CHAR(300);
  DECLARE "addr1" CHAR(40);
  DECLARE "addr2" CHAR(40);
  DECLARE "addr3" CHAR(40);
  DECLARE "town" CHAR(30);
  DECLARE "county" CHAR(30);
  DECLARE "country" CHAR(30);
  DECLARE "postcode" CHAR(30);
  DECLARE "Separator" CHAR(2);
  DECLARE "PrePostCodeSeparator" CHAR(2);
  /*
Set the seperator for block or line
*/
  IF "style" = 'B' THEN
    SET "Separator" = "char"(13)+"char"(10);
    SET "PrePostCodeSeparator" = "Separator"
  ELSE SET "Separator" = ', ';
    SET "PrePostCodeSeparator" = ' '
  END IF;
  /*
Fetch address fields
*/
  SELECT "addr1","addr2","addr3","town","county","country","postcode" INTO
"addr1",
  "addr2","addr3","town","county","country","postcode" FROM
"iqacaccountsettings"
```



```
WHERE "accountcode" = "reqAccountCode" AND "ledgerid" = 'Purchase';
/*
If capitalise option is set, capitalise town.
*/
IF "Capitalise" = 1 THEN SET "town" = "upper"("Town")
END IF;
/*
Build Formatted Address
*/
IF "isnull"("addr1",'') <> '' THEN SET "FormattedAddress" =
"FormattedAddress" || "trim"("addr1")
END IF;
IF "isnull"("FormattedAddress",'') <> '' AND "isnull"("addr2",'') <> ''
THEN SET "FormattedAddress" = "FormattedAddress" || "Separator"
END IF;
IF "isnull"("addr2",'') <> '' THEN SET "FormattedAddress" =
"FormattedAddress" || "trim"("addr2")
END IF;
IF "isnull"("FormattedAddress",'') <> '' AND "isnull"("addr3",'') <> ''
THEN SET "FormattedAddress" = "FormattedAddress" || "Separator"
END IF;
IF "isnull"("addr3",'') <> '' THEN SET "FormattedAddress" =
"FormattedAddress" || "trim"("addr3")
END IF;
IF "isnull"("FormattedAddress",'') <> '' AND "isnull"("town",'') <> ''
THEN SET "FormattedAddress" = "FormattedAddress" || "Separator"
END IF;
IF "isnull"("town",'') <> '' THEN SET "FormattedAddress" =
"FormattedAddress" || "trim"("town")
END IF;
IF "isnull"("FormattedAddress",'') <> '' AND "isnull"("county",'') <> ''
THEN SET "FormattedAddress" = "FormattedAddress" || "Separator"
END IF;
IF "isnull"("county",'') <> '' THEN SET "FormattedAddress" =
"FormattedAddress" || "trim"("county")
END IF;
IF "isnull"("FormattedAddress",'') <> '' AND "isnull"("country",'') <> ''
THEN SET "FormattedAddress" = "FormattedAddress" || "Separator"
END IF;
IF "isnull"("country",'') <> '' THEN SET "FormattedAddress" =
"FormattedAddress" || "trim"("country")
END IF;
IF "isnull"("FormattedAddress",'') <> '' AND "isnull"("postcode",'') <> ''
THEN SET "FormattedAddress" = "FormattedAddress" || "PrePostCodeSeparator"
END IF;
IF "isnull"("postcode",'') <> '' THEN SET "FormattedAddress" =
"FormattedAddress" || "trim"("postcode")
END IF;
```



```
RETURN "FormattedAddress"  
END  
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_formatselfbilladdress

Last update: **2026/08/07 19:24**

