



pears.GenerateContactEventWithEmailLog



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
CREATE PROCEDURE "pears"."GenerateContactEventWithEmailLog"(  
  /* Application Maintained Function / Procedure - DO NOT EDIT*/  
  IN "pcontacteventid" CHAR(20),  
  IN "pstaffid" CHAR(20),IN "pcontactdate" DATE,IN "pclasscode" CHAR(2),IN  
  "ppersonid" CHAR(20) DEFAULT NULL,  
  IN "pvacancyid" CHAR(20) DEFAULT NULL,IN "pemploymentid" CHAR(20) DEFAULT  
  NULL,IN "pprogressid" CHAR(20) DEFAULT NULL,  
  IN "pplacementid" CHAR(20) DEFAULT NULL,IN "pcontacttime" TIME DEFAULT  
  NULL,  
  IN "pdescription" CHAR(100) DEFAULT NULL,IN "poutcome" CHAR(50) DEFAULT  
  NULL,IN "pwho" CHAR(1) DEFAULT NULL,  
  IN "pnotes" long VARCHAR DEFAULT NULL,IN "plettertext" long VARCHAR  
  DEFAULT NULL,IN "pfollowup" SMALLINT DEFAULT 0,  
  IN "pwpdoc" CHAR(10) DEFAULT NULL,IN "pcallbackdate" DATE DEFAULT NULL,IN  
  "pWhenEntered" TIMESTAMP DEFAULT CURRENT TIMESTAMP,  
  IN "pWhoEntered" CHAR(20) DEFAULT NULL,IN "pcallbacktime" TIME DEFAULT  
  NULL,  
  IN "ppriority" SMALLINT DEFAULT 5,IN "pSynetyGUID" CHAR(100) DEFAULT NULL,  
  IN "pspeciality" CHAR(50) DEFAULT NULL,IN "pforenames" CHAR(30) DEFAULT  
  NULL,IN "psurname" CHAR(30) DEFAULT NULL,  
  IN "pDirection" CHAR(3) DEFAULT 'OUT',IN "pMethod" CHAR(10) DEFAULT  
  'EMAIL',IN "pWhenSent" TIMESTAMP DEFAULT CURRENT TIMESTAMP,  
  IN "pRecipients" long VARCHAR DEFAULT NULL,IN "pAttachments" long VARCHAR  
  DEFAULT NULL,IN "pdivisionid" CHAR(20) DEFAULT NULL )  
BEGIN  
  INSERT INTO "contactevent"(  
    "contacteventid","personid","staffid","vacancyid","employmentid","progressid"  
    , "placementid","contactdate","contacttime",  
    "description","outcome","classcode","who","notes","lettertext","followup","w  
    pdoc","callbackdate","divisionid","WhenEntered","WhoEntered",  
    "callbacktime","priority","SynetyGUID","speciality","forenames","surname" )  
  VALUES  
    (  
      "pcontacteventid","ppersonid","pstaffid","pvacancyid","pemploymentid","pprog  
      ressid","pplacementid","pcontactdate","pcontacttime",  
      "pdescription","poutcome","pclasscode","pwho","pnotes","plettertext","pfollowup","p  
      wpdoc","pcallbackdate","pdivisionid","pWhenEntered","pWhoEntered","pcallbacktime","ppriority","pSynetyGUID","pspeciality","pforenames","psurname"
```



```
"pdescription", "poutcome", "pclasscode", "pwho", "pnotes", "plettertext", "pfollowup", "pwpdoc", "pcallbackdate", "pdivisionid", "pWhenEntered", "pWhoEntered", "pcallbacktime", "ppriority", "pSynetyGUID", "pspeciality", "pforenames", "psurname" ) ;  
CALL  
"GenerateContactEventEmailLog" ("pContactEventid", "pWhenSent", "pRecipients", "pAttachments", "pDirection", "pMethod")  
END  
GO  
  
COMMENT TO PRESERVE FORMAT ON PROCEDURE  
"pears"."GenerateContactEventWithEmailLog" IS  
{CREATE PROCEDURE GenerateContactEventWithEmailLog  
  
/* Application Maintained Function / Procedure - DO NOT EDIT*/  
  
(IN "pcontacteventid" CHAR(20) ,  
    IN "pstaffid" CHAR(20) , IN "pcontactdate" DATE , IN "pclasscode" CHAR(2) ,  
IN "ppersonid" CHAR(20) DEFAULT NULL ,  
    IN "pvacancyid" CHAR(20) DEFAULT NULL , IN "pemploymentid" CHAR(20) DEFAULT  
NULL , IN "pprogressid" CHAR(20) DEFAULT NULL ,  
    IN "pplacementid" CHAR(20) DEFAULT NULL , IN "pcontacttime" TIME DEFAULT  
NULL ,  
    IN "pdescription" CHAR(100) DEFAULT NULL , IN "poutcome" CHAR(50) DEFAULT  
NULL , IN "pwho" CHAR(1) DEFAULT NULL ,  
    IN "pnotes" LONG VARCHAR DEFAULT NULL , IN "plettertext" LONG VARCHAR DEFAULT  
NULL , IN "pfollowup" SMALLINT DEFAULT 0 ,  
    IN "pwpdoc" CHAR(10) DEFAULT NULL , IN "pcallbackdate" DATE DEFAULT NULL ,  
IN "pWhenEntered" TIMESTAMP DEFAULT CURRENT_TIMESTAMP ,  
    IN "pWhoEntered" CHAR(20) DEFAULT NULL , IN "pcallbacktime" TIME DEFAULT  
NULL ,  
    IN "ppriority" SMALLINT DEFAULT 5 , IN "pSynetyGUID" CHAR(100) DEFAULT  
NULL ,  
    IN "pspeciality" CHAR(50) DEFAULT NULL , IN "pforenames" CHAR(30) DEFAULT  
NULL , IN "psurname" CHAR(30) DEFAULT NULL ,  
    IN "pDirection" CHAR(3) DEFAULT 'OUT' , IN "pMethod" CHAR(10) DEFAULT  
'EMAIL' , IN "pWhenSent" TIMESTAMP DEFAULT CURRENT_TIMESTAMP ,  
    IN "pRecipients" long VARCHAR DEFAULT NULL , IN "pAttachments" long VARCHAR  
DEFAULT NULL , IN "pdivisionid" CHAR(20) DEFAULT NULL )  
BEGIN  
    INSERT INTO contactevent (   
contacteventid, personid, staffid, vacancyid, employmentid, progressid, placementi  
d, contactdate, contacttime,   
description, outcome, classcode, who, notes, lettertext, followup, wpdoc, callbackda  
te, divisionid, WhenEntered, WhoEntered,   
    callbacktime, priority, SynetyGUID, speciality, forenames, surname )  
VALUES (pcontacteventid, ppersonid, pstaffid, pvacancyid, pemploymentid, pprogress  
id, pplacementid, pcontactdate, pcontacttime,
```



```
pdescription,poutcome,pclasscode,pwho,pnotes,plettertext,pfollowup,pwpdoc,pc  
allbackdate,pdivisionid,pWhenEntered,pWhoEntered,  
    pcallbacktime,ppriority,pSynetyGUID,pspeciality,pforenames,psurname);  
    CALL GenerateContactEventEmailLog(pContactEventid, pWhenSent, pRecipients,  
pAttachments, pDirection, pMethod);  
END  
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_generatecontacteventwithemaillog

Last update: **2026/08/07 19:24**

