



pears.GenerateKeyname



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GenerateKeyname" IS
{CREATE FUNCTION pears.GenerateKeyname(IN x CHAR(100))
RETURNS CHAR(100)
BEGIN
    DECLARE w1 CHAR(100);
    DECLARE wn CHAR(100);
    DECLARE c CHAR(1);
    DECLARE i INTEGER;
    SET x=TRIM(x);
    SET i=charindex("char"(32),x);
    IF i > 0 THEN
        SET w1="left"(x,i-1);
        IF w1 IN('mr','ms','miss','mrs','mr.','ms.','mrs.') THEN
            SET x="right"(x,LENGTH(x)-i)
        END IF
    END IF;
    SET i=LENGTH(x);
loop1: loop
    SET c=substr(x,i,1);
    IF c = "char"(32) THEN
        RETURN makekeyname("right"(x,LENGTH(x)-i)+' '+'left"(x,i-1))
    END IF;
    SET i=i-1;
    IF i <= 0 THEN
        leave loop1
    END IF
END loop loop1;
RETURN x
END
}
```



From:
<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_generatekeyname

Last update: **2026/08/07 19:24**

