



pears.GetCompanyGroupHead



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetCompanyGroupHead" IS
{CREATE FUNCTION GetCompanyGroupHead

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN CompID CHAR(20))
RETURNS CHAR(20)
BEGIN
    DECLARE coid CHAR(20);
    DECLARE oldcoid CHAR(20);
    DECLARE lc INTEGER;
    SELECT parentcompanyid INTO coid FROM company WHERE companyid = compid;
    IF coid IS NULL THEN
        RETURN compid
    END IF;
    SET oldcoid=NULL;
    SET lc=1;
    while(coid IS NOT NULL) AND(lc < 1000) loop
        SET oldcoid=coid;
        SET lc=lc+1;
        SELECT parentcompanyid INTO coid FROM company WHERE companyid = coid
    END loop;
    RETURN oldcoid
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getcompanygrouphead

Last update: 2026/08/07 19:24

