



pears.GetEmployeePhoneInBlock



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetEmployeePhoneInBlock" IS
{CREATE FUNCTION GetEmployeePhoneInBlock

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN reqemploymentid CHAR(20))
RETURNS long VARCHAR
BEGIN
    DECLARE phones long VARCHAR;
    DECLARE newline CHAR(2);
    DECLARE loopcounter tinyint;
    DECLARE tab CHAR(1);
    DECLARE TabString CHAR(2);
    SET newline="char"(13)+"char"(10);
    SET phones='';
    SET loopcounter=0;
    SET tab="char"(9);
    FOR fetchfor AS fetchcursor no scroll cursor FOR
        SELECT phonetype."name" AS nextname,phone.number AS nextnumber FROM
phone KEY JOIN
    phonetype WHERE phone.who='CP' AND whoid=reqemploymentid ORDER BY
    phone.whoid ASC,phonetype.sortorder ASC,phonetype."name" ASC FOR READ
ONLY do
    IF loopcounter>0 THEN
        SET phones=phones||newline
    END IF;
    IF LENGTH(nextname) < 8 THEN SET TabString=Tab+Tab
    ELSE SET TabString=Tab
    END IF;
    SET phones=phones||nextname||tabstring||nextnumber;
    SET loopcounter=loopcounter+1 END FOR;
    RETURN phones
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getemployeephoneinblock

Last update: **2026/08/07 19:24**

