



pears.GetPayOrCharge



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetPayOrCharge" IS
{CREATE FUNCTION GetPayOrCharge

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN PayOrCharge CHAR(1),IN PlacOrVac CHAR(1),IN ID CHAR(20))
RETURNS CHAR(20)
BEGIN
    DECLARE pay DOUBLE;
    DECLARE istemp SMALLINT;
    IF placorvac = 'P' THEN
        SELECT isnull(temp,0),salary INTO istemp,pay FROM placement WHERE
placementid = id
    ELSE
        SELECT isnull(temp,0),salary INTO istemp,pay FROM vacancy WHERE
vacancyid = id
    END IF;
    IF istemp = 0 THEN
        IF payorcharge = 'P' THEN
            RETURN commathousands(pay)
        ELSE
            RETURN ''
        END IF
    ELSE
        RETURN TRIM(str(gettemprate(payorcharge,placorvac,id),20,2))
    END IF
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getpayorcharge

Last update: **2026/08/07 19:24**

