



pears.GetPlacementTheirRef



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetPlacementTheirRef" IS
{CREATE FUNCTION GetPlacementTheirRef

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN persid CHAR(20),IN vacid CHAR(20))
RETURNS CHAR(50)
BEGIN
  DECLARE rv CHAR(50);
  SET rv=NULL;
  forstat: FOR forlab AS curs no scroll cursor FOR
    SELECT placement.theirref FROM placement KEY JOIN employment WHERE
      placement.vacancyid = vacid AND employment.personid = persid AND
      placement.temp <> 0 ORDER BY isnull(employment.leavedate,CURRENT
DATE+3650) DESC FOR READ ONLY do
    SET rv=theirref;
  leave forstat END FOR;
  IF TRIM(isnull(rv,'')) = '' THEN
    SELECT theirref INTO rv FROM vacancy WHERE vacancyid = vacid
  END IF;
  RETURN(rv)
END
}
```

From:
<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:
https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getplacementtheirref

Last update: 2026/08/07 19:24

