



pears.GetPropertiesText



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetPropertiesText" IS
{CREATE FUNCTION GetPropertiesText

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(
  IN "PropertyType" CHAR(1),IN "HeaderText" long VARCHAR,IN "ConID" INTEGER
)
RETURNS long VARCHAR
BEGIN
  -- PropertyType - C for connection (requires connectionid), D for
  database, E for engine / server, W engine / server window messages
  DECLARE "PropsText" long VARCHAR;
  DECLARE "NewLine" CHAR(2);
  DECLARE "Tab" CHAR(1);
  SET "NewLine" = "char"(13)+"char"(10);
  SET "Tab" = "char"(9);
  CASE "PropertyType"
  WHEN 'C' THEN
    SELECT "list"("string"("PropName",' =
    ',' "Value", "Tab", '(' , "PropDescription", ')')', "NewLine" ORDER BY "PropName"
    ASC) INTO "PropsText" FROM "sa_conn_properties_by_name"("ConID")
  WHEN 'D' THEN
    SELECT "list"("string"("PropName",' =
    ',' "Value", "Tab", '(' , "PropDescription", ')')', "NewLine" ORDER BY "PropName"
    ASC) INTO "PropsText" FROM "sa_db_properties"("DB_ID"())
  WHEN 'E' THEN
    SELECT "list"("string"("PropName",' =
    ',' "Value", "Tab", '(' , "PropDescription", ')')', "NewLine" ORDER BY "PropName"
    ASC) INTO "PropsText" FROM "sa_eng_properties"()
  WHEN 'W' THEN
    SELECT "list"("string"("dateformat"("msg_time",'yyyy-mm-dd
    hh:nn:ss'), "Tab", "msg_text"), "NewLine" ORDER BY "msg_id" ASC) INTO
    "PropsText" FROM "sa_server_messages"()
  END CASE;
```



```
RETURN("trim"("HeaderText" || "NewLine" || "NewLine" || "PropsText"))  
END  
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getpropertytext

Last update: **2026/08/07 19:24**

