



pears.GetQuestAnswer



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetQuestAnswer" IS
{CREATE FUNCTION GetQuestAnswer

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN tagloc CHAR(3),IN tagid CHAR(3),IN parentid CHAR(20))
RETURNS long VARCHAR
BEGIN
  DECLARE rv long VARCHAR;
  DECLARE i INTEGER;
  SET rv=getquesttext(tagloc,tagid,parentid);
  IF rv IS NULL THEN
    RETURN(NULL)
  END IF;
  SET i=locate(rv,"char"(13));
  IF i > 0 THEN
    SET rv="left"(rv,i-1)
  END IF;
  SET i=locate(rv,"char"(9));
  IF i >= LENGTH(rv) THEN
    RETURN('')
  END IF;
  IF i > 0 THEN
    SET rv=stuff(rv,1,i,'')
  END IF;
  RETURN(rv)
END
}
```



From:

<https://iqxusers.co.uk/iqxhelp/> - **iqx**

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_getquestanswer

Last update: **2026/08/07 19:24**

