



pears.GetTempName



Generated schema reference. Regenerate this page from the SQL unload; keep hand-maintained business notes in the narrative namespace.

Original SQL

```
COMMENT TO PRESERVE FORMAT ON PROCEDURE "pears"."GetTempName" IS
{CREATE FUNCTION GetTempName

/* Application Maintained Function / Procedure - DO NOT EDIT*/

(IN persid CHAR(20))
RETURNS CHAR(60)
BEGIN
    DECLARE rv CHAR(60);
    SELECT string (IF EXISTS (SELECT * FROM wpkglobalswitchsetting WHERE
wpkglobalswitchid = 'USEFULLNAME' AND location = 'Global' AND VALUE = 'Y')
THEN person.name ELSE
    ifnull(person.surname, person.name, string(person.surname, ',
', firstword(person.forenames))) endif,
    (SELECT string(' (', name, ')') FROM company WHERE companyid = (SELECT
secondaryagencyid FROM pay_employee WHERE personid = persid))
    ) INTO rv FROM person WHERE personid = persid;
    RETURN rv
END
}
```

From:

<https://iqxusers.co.uk/iqxhelp/> - iqx

Permanent link:

https://iqxusers.co.uk/iqxhelp/doku.php?id=database:procedures:pears_gettempname

Last update: 2026/08/07 19:24

